



COATED PRODUCTS, INC.
Special Application Acrylic Sheet

www.Techplast.com

Hard Coat/Anti-Static TechPlast XT Sheet Finish Specification

CHARACTERISTIC	SPECIFICATION
Fibers	
Under 0.030" or .75mm	Any amount
0.031" 0.050" or .75mm-1.25mm	2 per square ft.
0.051" 0.080" or 1.25mm-2mm	1 per square ft.
Over 0.080" or 2mm	None
PITS and SPECKLES	
Under 0.020" or .5mm	Any amount
0.021" 0.030" or .5mm-.75mm	10 per sheet
0.031" 0.050" or .75mm-1.25mm	5 per sheet
0.051" 0.080" or 1.25mm-2mm	2 per sheet
Over 0.080" or 2mm	None
*BLACK SPECKS	
Under .0118" or .3mm	Any amount
0.0119" 0.0197" or .3mm-.5mm	1 or less per sq.ft.
Greater than 0.0197" or .5mm	None
SCRATCHES and SCUFFS	
Under 0.060" or 1.5mm	Any amount
0.061" 0.200" or 1.5mm-5mm	2 per sheet
Over 0.200" or 5mm	None

*Anything not visible at 6 feet or 1828mm is acceptable.

*These specifications will be used for all flowcoated sheet no matter what the application will be.

Issue Date: July 2005